

Declaration of Performance (DoP)

NO. 90175601-CPR-20130702	
1. Product Type:	Inset appliance
2. Type, batch or serial number:	DSA 3-2, DSA 3-5
3. Intended use of the product:	Inset appliance without hot water supply
4. Name and Address of the manufacturer:	Scan AS Glassvænget 3-9 5492 Vissenbjerg
5. Contact address:	No relevance
6. AVCP: <i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i>	System 3
7. Notified body: FSPS-WA 1769-EN	RWE NB-No 1427 FSPS-Wa 1473 EN
8. Declared performance:	
Harmonized technical specification	EN 13229
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Front = 1100 Floor = 300 <i>Combustable materials inside the surround must be covered by insulation as described in the manual</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,10 %] NOx [119 mg/m ³] OGC [126 mgC/m ³] Dust [32 mg/m ³]
Surface temperature	Pass

Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [278°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	6 kW
Room heating output	-
Water heating output	-
Energy efficiency	η [77%]

DECLARATION:


The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Morten Bach
R&D LAB

(Name and function)

Vissenbjerg September 03, 2013



(Place and date of issue)

(Signature)